

Direct DC Solar Pump


- No Need Pump Controller
- Get Large Flow With Few Solar Panel
- High Efficiency

Application

Take place of AC pump or engine pump to save total cost.

Irrigation: Transfer water from nearby water sources such as lake, rivers to irrigate the crops.

Livestock, Garden Fountains, Home Supply: Provide water supply with a cost-effective and easy way.



DCP Series

Direct DC Peripheral Solar Pump



DCP18-12V
DCP37-24V



DCP55-48V


Application

- Transfer clean water or other liquids similar to water in physical and chemical properties
- No electricity area's domestic water lifting
- Off grid solar irrigation system

Features

- Brass impeller
- AISI304 Pump shaft
- 100% Copper winding
- DC Brush motor
- Work without controller
- Can be powered by battery & solar power directly


Identification Codes



Technical Data

Model	Output Power		DC Voltage Range	Recommended Solar Panel	Max. Current	Max. Suction	Inlet/Outlet	Max. Flow	Max. Head
	kW	HP							
DCP18-12V	0.18	0.25	12~24 V	180Wx2 In parallel	20 A	8 m	1" x 1"	2.5 m³/h	23 m
DCP37-24V	0.37	0.5	24~48 V	330Wx2 In parallel	20 A			2.3 m³/h	46 m
DCP55-48V	0.55	0.75	48~72 V	180Wx4 In series	10 A			3.3 m³/h	35 m

Hydraulic Performance Curves



QDX Series

Direct DC Submersible Pump



1.1kW Impeller
1.3kW Impeller


Application

- Transfer clean water or other liquids similar to water in physical and chemical properties.
- Transfer light sewage water (Only 1.3kw model)
- No electricity area's domestic water lifting
- Off grid solar irrigation system

Features

- Aluminum impeller
- Cast iron pump body
- AISI304 Pump shaft
- 100% Copper winding
- DC Brush motor
- Work without controller
- Can be powered by battery & solar power directly


Identification Codes



Technical Data

Model	Output Power		DC Voltage Range	Recommended Solar Panel	Max. Current	Discharge	Max. Flow	Max. Head
	kW	HP						
QDX8-18-1.1DC	1.1	1.5	110~150 V	330Wx4 In series	10 A	2"	18 m³/h	26 m
QDX25-5-1.3DC	1.3	1.8	150~200 V	330Wx5 In series	10 A	3"	51 m³/h	11 m

Hydraulic Performance Curves



High Efficiency Solar Module 180W 330W



Features

- High Efficiency**
MWT back contact cell and modules with busbar-free design and higher efficiency
- Superior Warranty**
The only single-glass module with 30-year power warranty by LLOYD'S & PICC worldwide
- High ROI**
Higher return on investment with higher power output
- High Reliability**
Conductive back sheet 2D encapsulation without soldering, resulted lower degradation under multiple extreme testing condition
- Aesthetic Design**
Busbar-free design, unique and graceful finger pattern on the solar cell surface, customized pattern design also available
- Lead Free**
Eco-friendly PV design achieves Lead-free without soldering materials

High Efficiency Solar Module

Spec	Model	Unit	Electrical Characteristics at Standard Test Condition(STC)		Electrical Characteristics at Nominal Module Operating Temp. (NMOT)	
			SPP180N60H	SPP330N60H	SPP180N60H	SPP330N60H
Max. Power (Pm)		W	180	330	133.39	248
Power Tolerance		W	0 ~ +5W		-	
Max. Power Voltage (Vmp)		V	19.9	32.5	17.1	29.8
Max. Power Current (Imp)		A	9.09	10.15	7.69	8.32
Open Circuit Voltage (Voc)		V	23.6	40	17.4	36.6
Short Circuit Current (Isc)		A	9.79	10.58	7.61	8.69
Module Efficiency		%	18%	19.30%	-	

STC: AM=1.5, Irradiation 1000W/m²,Module Temperature 25℃
NMOT: Irradiation 800W/m²,Ambient temperature 20℃ , Wind Speed 1m/s. Ask LEO for whole solar module catalogue, If you need other power.

Temperature Coefficient

Spec	Model	SPP180N60H	SPP330N60H
Nominal Module Operating Temperature		45 ± 2℃	43 ± 2℃
Temperature coefficient of Pmax		-0.36%/℃	-0.36%/℃
Temperature coefficient of Voc		-0.32%/℃	-0.28%/℃
Temperature coefficient of Isc		0.06%/℃	0.06%/℃

Operating Conditions

Spec	Model	SPP180N60H	SPP330N60H
Max System Voltage		1500V(TUV)	
Max Fuse Rated Current		15A	
Operating Temperature Range		-40℃ +85℃	
Mechanical Load		5400Pa (front) /2400Pa (rear)	
Max Allowable Hail Load		φ 25mm hail, from 1m of distance at 23 m/s	


Mechanical Characteristics

Spec	Model	SPP180N60H	SPP330N60H
Solar Cell Encapsulant		EVA	
Juntion Box		IP68	
Colar Cell Array (Mono)		60 PCS(10x6)	36 PCS(4x9)
Glass Type		3.2mm High Transmittance Anti-reflective Coated Tempered Glass	
Cable		0.9m length 4mm²	1m length 4mm²
Frame		Anodized Aluminum Alloy / Silver	
Connector		MC4 Compatible	
Weight		11.5kg	19.5kg
Dimension (LxWxH)		1482x674x35mm	1680x1016x30mm
Package		30 pcs/pallet	31 pcs/pallet
40HQ Container		1350 pcs	924 pcs


Recommended Solar Panel Connection




DCP18-12: 180W x 2 Connection in parallel




DCP37-24V: 330W x 2 Connection in parallel




DCP55-48V: 180W x 4 Connection in series



QDX8-18-1.1DC: 330W x 4 Connection in series



QDX5-20-1.3DC: 330W x 5 Connection in series



LEO LEO GROUP PUMP(ZHEJIANG) CO.,LTD. (Stock code: 002131)

No.1, 3rd Street, East Industry Center, Wenling, Zhejiang, China, 317511
Tel: +86-576-8998 6360 Fax: +86-576-8998 9898 E-mail: export@leogroup.cn www.leogroup.cn

LEO reserves all the right of products modification without prior notification.